



Threaded Nozzles – Full Cone Series S Molded Plastic



Polypropylene

PVDF

Non-Pigmented



Thread	Length D (mm)	Dim. H (mm)	Dim. L (mm)
1/8F	16	14	21
1/4F	16	14	24
3/8F	20	17	28

SPRAY CHARACTERISTICS:

Full cone spray pattern, with uniform distribution throughout the cone.

CONSTRUCTION:

These nozzles are injection molded and contain a patented insert with larger flow passages than older styles, and are less susceptible to clogging. Standard materials are polypropylene, and PVDF, and all materials are color-coded for easy identification. Non-pigmented versions are also available.

TYPICAL APPLICATIONS:

- Chemical Processing
- Cooling Sprays
- Foam Breaking
- Continuous Casting

MATERIALS AVAILABLE:

POLYPROPYLENE (LL) - (Green) excellent chemical and corrosion resistance. Useful up to 80°C.

NATURAL POLYPROPYLENE (LN) - non-pigmented for optimum purity.

PVDF (KK) - (Red) excellent durability and abrasion resistance and is inert to most chemicals. Useful up to 150°C.

NATURAL PVDF (KN) - non-pigmented for optimum purity.

Model Number	Thread BSPT	MAX. FREE PASSAGE (mm)	CAPACITY (L/min) AT VARIOUS PRESSURES (bar)												Spray Angle @		
			0.2 bar	0.3 bar	0.5 bar	0.7 bar	1 bar	1.5 bar	2 bar	3 bar	4 bar	5 bar	6 bar	8 bar	0.5 bar	1.5 bar	5 bar
1/8 S1	1/8"	0.84	--	--	--	--	0.46	0.56	0.64	0.79	0.91	1.02	1.12	1.29	--	55°	52°
1/8 S1.5	1/8"	1.17	--	--	--	0.57	0.68	0.84	0.97	1.18	1.37	1.53	1.67	1.93	--	65°	57°
1/8 S2	1/8"	1.30	--	--	0.64	0.76	0.91	1.12	1.29	1.58	1.82	2.04	2.23	2.58	54°	59°	60°
1/8 S3	1/8"	1.30	--	0.75	0.97	1.14	1.37	1.67	1.93	2.37	2.73	3.06	3.30	3.90	50°	53°	60°
1/8 S3.5	1/8"	1.30	0.71	0.87	1.13	1.33	1.60	1.95	2.26	2.76	3.20	3.60	3.90	4.50	48°	58°	61°
1/8 S5	1/8"	1.63	1.02	1.25	1.61	1.91	2.28	2.79	3.20	3.90	4.60	5.10	5.60	6.40	60°	75°	70°
1/8 S6	1/8"	1.63	1.22	1.50	1.93	2.29	2.73	3.30	3.90	4.70	5.50	6.10	6.70	7.70	67°	72°	70°
¼ S5	1/4"	2.06	1.02	1.25	1.61	1.91	2.28	2.79	3.20	3.90	4.60	5.10	5.60	6.40	58°	68°	62°
¼ S6.5	1/4"	2.31	1.32	1.62	2.09	2.48	2.96	3.60	4.20	5.10	5.90	6.60	7.30	8.40	48°	56°	50°
¼ S7.5	1/4"	2.31	1.53	1.87	2.42	2.86	3.40	4.20	4.80	5.90	6.80	7.60	8.40	9.70	55°	65°	48°
¼ S8.5	1/4"	2.31	1.73	2.12	2.74	3.20	3.90	4.70	5.50	6.70	7.70	8.70	9.50	11.0	58°	65°	63°
¼ S10	1/4"	2.31	2.04	2.50	3.20	3.80	4.60	5.60	6.40	7.90	9.10	10.2	11.2	12.9	60°	65°	62°
¼ S14	1/4"	2.31	2.85	3.50	4.51	5.30	6.40	7.80	9.00	11.1	12.8	14.3	15.6	18.0	78°	85°	75°
3/8 S9.5	3/8"	2.59	1.94	2.37	3.06	3.60	4.30	5.30	6.10	7.50	8.70	9.70	10.6	12.2	58°	68°	62°
3/8 S10	3/8"	2.59	2.04	2.50	3.02	3.80	4.60	5.60	6.40	7.90	9.10	10.2	11.2	12.9	55°	65°	50°
3/8 S15	3/8"	2.59	2.85	3.50	4.80	5.30	6.80	8.40	9.70	11.8	13.7	15.3	16.7	19.3	63°	65°	60°