

# Other Types of Nozzles and Accessories – Series WN



### SPRAY CHARACTERISTICS:

Available in flat fan and solid stream (0 degree) models, these self-cleaning nozzles reduce shower maintenance. By reducing the supplied pressure, an internal piston retracts to purge fibers and other suspended solids from the clogged nozzle.

### CONSTRUCTION:

Standard material of construction is 316 stainless steel

Standard thread size is 1 1/8" - 20.

### TYPICAL APPLICATIONS:

- Cleaning Fabric (wire)
- Cleaning Felts
- Pre-wetting Showers
- Knock-off Showers
- Lubrication Shower

Model	MAX. FREE PASSAGE (mm)	CAPACITY AT VARIOUS PRESSURES (bar)						
		3 bar	4 bar	5 bar	6 bar	15 bar	40 bar	60 bar
WN14	0.36	0.109	0.125	0.140	0.154	0.243	0.396	0.485
WN28	0.71	0.434	0.501	0.561	0.614	0.971	1.585	1.942
WN33	0.84	0.632	0.729	0.815	0.893	1.412	2.306	2.824
WN40	1.02	0.908	1.048	1.172	1.284	2.030	3.315	4.060
WN55	1.40	1.579	1.823	2.038	2.233	3.530	5.770	7.060
WN70	1.78	2.645	3.054	3.410	3.740	5.910	9.660	11.830
WN94	2.39	4.740	5.470	6.110	6.700	10.590	17.300	21.180
WN125	3.18	7.890	9.120	10.190	11.160	17.650	28.830	35.300