


Other Types of Nozzles and Accessories – Series WA



Model	Dim. H (mm)	Dim. L (mm)
WA	38	41

SPRAY CHARACTERISTICS:

Available in flat fan and solid stream (0 degree) models, these self-cleaning nozzles reduce shower maintenance. By reducing the supplied pressure, an internal piston retracts to purge fibers and other suspended solids from the clogged nozzle.

CONSTRUCTION:

Standard material of construction is 316 stainless steel.

TYPICAL APPLICATIONS:

- Cleaning Fabric (wire)
- Cleaning Felts
- Pre-wetting Showers
- Knock-off Showers
- Lubrication Shower

Spray Angle	Model	CAPACITY AT VARIOUS PRESSURES (bar)													
		1.5 bar	2 bar	2.5 bar	3 bar	4 bar	5 bar	6 bar	7 bar	8 bar	9 bar	10 bar	12 bar	15 bar	18 bar
0°	WA0002	0.56	0.64	0.72	0.79	0.91	1.02	1.12	1.21	1.29	1.37	1.44	1.58	1.77	1.93
	WA0006	1.67	1.93	2.16	2.37	2.73	3.06	3.3	3.6	3.9	4.1	4.3	4.7	5.3	5.8
	WA0008	2.23	2.58	2.88	3.2	3.6	4.1	4.5	4.8	5.2	5.5	5.8	6.3	7.1	7.7
	WA0010	2.79	3.2	3.6	3.9	4.6	5.1	5.6	6	6.4	6.8	7.2	7.9	8.8	9.7
15°	WA1506	1.67	1.93	2.16	2.37	2.73	3.06	3.3	3.6	3.9	4.1	4.3	4.7	5.3	5.8
30°	WA3005	1.4	1.61	1.8	1.97	2.28	2.55	2.79	3.01	3.2	3.4	3.6	3.9	4.4	4.8
	WA3014	3.9	4.5	5	5.5	6.4	7.1	7.8	8.4	9	9.6	10.1	11.1	12.4	13.5
40°	WA4012	3.3	3.9	4.3	4.7	5.5	6.1	6.7	7.2	7.7	8.2	8.6	9.5	10.6	11.6
	WA4014	3.9	4.5	5	5.5	6.4	7.1	7.8	8.4	9	9.6	10.1	11.1	12.4	13.5
	WA4032	8.9	10.3	11.5	12.6	14.6	16.3	17.9	19.3	20.6	21.9	23.1	25.3	28.2	30.9
45	WA4516	4.5	5.2	5.8	6.3	7.3	8.2	8.9	9.6	10.3	10.9	11.5	12.6	14.1	15.5
	WA4525	7	8.1	9	9.9	11.4	12.7	14	15.1	16.1	17.1	18	19.7	22.1	24.2
50°	WA5032	8.9	10.3	11.5	12.6	14.6	16.3	17.9	19.3	20.6	21.9	23.1	25.3	28.2	30.9
60°	WA6016	4.5	5.2	5.8	6.3	7.3	8.2	8.9	9.6	10.3	10.9	11.5	12.6	14.1	15.5
	WA6038	10.6	12.2	13.7	15	17.3	19.4	21.2	22.9	24.5	26	27.4	30	34	37
80°	WA8011	3.07	3.5	4	4.3	5	5.6	6.1	6.6	7.1	7.5	7.9	8.7	9.7	10.6
	WA8030	8.4	9.7	10.8	11.8	13.7	15.3	16.7	18.1	19.3	20.5	21.6	23.7	26.5	29
	WA8046	12.8	14.8	16.6	18.2	21	23.4	25.7	27.7	29.6	31.4	33	36	41	44
110°	WA11011	3.07	3.5	4	4.3	5	5.6	6.1	6.6	7.1	7.5	7.9	8.7	9.7	10.6
120°	WA12008	2.23	2.58	2.88	3.2	3.6	4.1	4.5	4.8	5.2	5.5	5.8	6.3	7.1	7.7
130°	WA13016	4.5	5.2	5.8	6.3	7.3	8.2	8.9	9.6	10.3	10.9	11.5	12.6	14.4	15.5
	WA13025	7	8.1	9	9.9	11.4	12.7	14	15.1	16.1	17.1	18	19.7	22.1	24.2