



Other Types of Nozzles and Accessories – Self Aligning Disc



TYPICAL APPLICATIONS:

WF Series shower nozzles are designed to work in a number of commercially available "shower" bar systems where a self-aligning replaceable nozzle disc is required.

The back protruding design permits the nozzle orifice to be cleaned from inside the header, using a rotating brush.


SPRAY CHARACTERISTICS:

Available in 30° and 60° flay V-shaped spray patterns, as well as zero (0) degree solid stream spray.

All flat V-shaped spray models are pre-aligned to a standard 7° offset angle to allow for spray overlap without interference from the adjacent nozzles.

CONSTRUCTION:

Standard material of construction for the spray disc is 317L stainless steel. A gasket is available for sealing the face between the nozzle disc and the body.



| Spray-angle @ 3 bar | MODEL NUMBER | CAPACITY (L/min) AT VARIOUS PRESSURES (bar) | | | | | | | |
|---------------------|--------------|---|-------|-------|-------|-------|--------|--------|--------|
| | | 1.5 bar | 3 bar | 4 bar | 5 bar | 6 bar | 12 bar | 25 bar | 40 bar |
| 0° Vollstrahl | WF00004 | 1.2 | 1.7 | 2 | 2.2 | 2.4 | 3.4 | 4.9 | 6.2 |
| | WF00007 | 0.2 | 0.3 | 0.3 | 0.4 | 0.4 | 0.6 | 0.8 | 1 |
| | WF00009 | 0.3 | 0.4 | 0.4 | 0.5 | 0.5 | 0.7 | 1 | 1.3 |
| | WF0001 | 0.4 | 0.5 | 0.6 | 0.7 | 0.7 | 1 | 1.5 | 1.9 |
| | WF0002 | 0.6 | 0.9 | 1.1 | 1.2 | 1.3 | 1.8 | 2.6 | 3.3 |
| | WF0003 | 0.9 | 1.3 | 1.5 | 1.7 | 1.8 | 2.6 | 3.8 | 4.8 |
| | WF0004 | 1.2 | 1.7 | 2 | 2.2 | 2.4 | 3.4 | 4.9 | 6.2 |
| | WF0008 | 2.2 | 3.1 | 3.6 | 4 | 4.4 | 6.2 | 9 | 11 |
| | WF0012 | 3.5 | 4.9 | 5.7 | 6.3 | 6.9 | 9.8 | 14 | 18 |
| | WF0020 | 5.5 | 7.8 | 9 | 10 | 11 | 16 | 23 | 29 |
| 30° | WF3002 | 0.6 | 0.9 | 1.1 | 1.2 | 1.3 | 1.8 | 2.6 | 3.3 |
| | WF3003 | 0.9 | 1.3 | 1.5 | 1.7 | 1.8 | 2.6 | 3.8 | 4.8 |
| | WF3004 | 1.2 | 1.7 | 2 | 2.2 | 2.4 | 3.4 | 4.9 | 6.2 |
| | WF3006 | 1.7 | 2.4 | 2.8 | 3.1 | 3.4 | 4.8 | 7 | 8.8 |
| | WF3008 | 2.2 | 3.1 | 3.6 | 4 | 4.4 | 6.2 | 9 | 11 |
| | WF3010 | 2.9 | 4 | 4.7 | 5.2 | 5.7 | 8.1 | 12 | 15 |
| | WF3012 | 3.5 | 4.9 | 5.7 | 6.3 | 6.9 | 9.8 | 14 | 18 |
| | WF3016 | 4.5 | 6.4 | 7.3 | 8.2 | 9 | 13 | 18 | 23 |
| | WF3020 | 5.5 | 7.8 | 9 | 10 | 11 | 16 | 23 | 29 |
| | 60° | WF6002 | 0.6 | 0.9 | 1.1 | 1.2 | 1.3 | 1.8 | 2.6 |
| WF6003 | | 0.9 | 1.3 | 1.5 | 1.7 | 1.8 | 2.6 | 3.8 | 4.8 |
| WF6004 | | 1.2 | 1.7 | 2 | 2.2 | 2.4 | 3.4 | 4.9 | 6.2 |
| WF6006 | | 1.7 | 2.4 | 2.8 | 3.1 | 3.4 | 4.8 | 7 | 8.8 |
| WF6008 | | 2.2 | 3.1 | 3.6 | 4 | 4.4 | 6.2 | 9 | 11 |
| WF6010 | | 2.9 | 4 | 4.7 | 5.2 | 5.7 | 8.1 | 12 | 15 |
| WF6012 | | 3.5 | 4.9 | 5.7 | 6.3 | 6.9 | 9.8 | 14 | 18 |
| WF6016 | | 4.5 | 6.4 | 7.3 | 8.2 | 9 | 13 | 18 | 23 |
| WF6020 | | 5.5 | 7.8 | 9 | 10 | 11 | 16 | 23 | 29 |
| WF6025 | | 7.3 | 10 | 12 | 13 | 15 | 21 | 30 | 37 |
| WF6031 | | 8.7 | 12 | 14 | 16 | 17 | 25 | 35 | 45 |
| WF6040 | | 11 | 16 | 18 | 20 | 22 | 32 | 46 | 58 |
| WF6049 | | 14 | 19 | 22 | 25 | 27 | 39 | 56 | 71 |
| WF6077 | | 22 | 31 | 36 | 40 | 44 | 62 | 90 | 114 |
| WF6099 | 28 | 39 | 45 | 50 | 55 | 78 | 113 | 143 | |
| WF60124 | 35 | 49 | 57 | 63 | 69 | 98 | 141 | 179 | |

WF FLAT STREAM NOZZLE

WF SOLID STREAM NOZZLE

